

The perfect balance of technology and design.



The perfect balance of technology and design in 12 innovative features.


Designed with the worker in mind, our unique technology allows for eight points of adjustability in this customizable, stylish eyewear.

They'll think you had these made just for them, and you'll know your worker are safe

- - HydroShield Coating
- 9 Base Lens
- Floating Nose Loop
- - Flexible Nose Pads
- - Soft Brow Frame MMT+
- - Indirect Venting System
- - Angle-Adjustable Ratchet Temple
- Flexible Temples MMT+
- 😟 Soft Temples & Nose Pads MMT+
- Wire-Core Temples
- 😟 Wrap Around Temples & Soft Tip Pads
 - MMT+
- 😟 Ultra-Light Frame



Honeywell HydroShield[®] Anti-Fog Coating



The dual action HydroShield anti-fog lens coating provides **more than 20X longer lasting fog-free performance** – even after extended wear and repeated cleanings – and provides **2X greater scratch-resistance*** than the current anti-fog coating.

- Permanently bonded to the lens
- Exceed 180 seconds of total fog free time
- No application
- No maintenance

*Comparative lens life text performed using a Bayer Abrasion Test method and may vary between environment and application.

RISKS

• General use and protection against impact (45m/s) – special protection against fogging

APPLICATIONS

• Suitable for all environments where fogging occurs, that is widely across industries – from construction, manufacturing, chemical, and utilities, to oil and gas – and across applications

Honeywell Avatar Specifications



| Technical Datas | | | |
|------------------------------------|---|--|--|
| Range | Spectacles | | |
| Lens Material | Polycarbonate | | |
| Frame Material | TPE | | |
| Frame color | Red & Black and Black | | |
| Lens Coating | Honeywell Hydroshield and Hard-Coat | | |
| Weight | 33 grams per eyewear | | |
| Certifications | EC Certificate Number 3053 - Standard(s): EN166:2001 - EC | | |
| Category PPE | 2 - Quality Assurance : ISO 9001 / 2000 | | |
| Delivery Information Selling units | 8 units per box , 80 units per case | | |

| Ref. | Description | Lens | Coating | Frame Marking | Lens Marking |
|---------|--|-------------|-------------|---------------|------------------|
| 1034831 | Honeywell Avatar Black / HydroShield coating/ Clear lens | ⊖ Clear | HydroShield | HON 166F | 2C-1.2 HON 1F KN |
| 1034832 | Honeywell Avatar Black / HydroShield coating/ Grey lens | • Grey | HydroShield | HON 166F | 5-3.1 HON 1F KN |
| 1034833 | Honeywell Avatar Black / HydroShield coating/ Amber lens | Amber | HydroShield | HON 166F | 2C-1.2 HON 1F KN |
| 1034834 | Honeywell Avatar Black / Hard Coating/ I/O lens | 1/0 | Hard Coat | HON 166F | 5-1.7 HON 1F |
| 1034835 | Honeywell Avatar Black / Hard Coating/ Blue mirror lens | Blue Mirror | Hard Coat | HON 166F | 5-3.1 HON 1F |
| 1034836 | Honeywell Avatar Black&Red / HydroShield coating/ Clear lens | ⊖ Clear | HydroShield | HON 166F | 2C-1.2 HON 1F KN |
| 1034837 | Honeywell Avatar Black&Red / HydroShield coating/ Grey lens | • Grey | HydroShield | HON 166F | 5-3.1 HON 1F KN |
| 1034838 | Honeywell Avatar Black&Red / Hard Coating/ I/O lens | 1/0 | Hard Coat | HON 166F | 5-1.7 HON 1F |

Lens markings

Optical class 1: no optical distortion (permanent wear authorised) Mechanical resistance F: impact: 45 m/s T: resistance guaranteed between -5 and 55°C K: Resistance to surface damage by fine particles N: Resistance to fogging Filter performance and area of application Code (area of application) 2 : UV filter 5 : sunlight filter Colour perception: C: colour perception unchanged Safety class: 1.2 to 6: level of filtering of visible light

HONEYWELL SAFETY PRODUCTS

UNITED KINGDOM

Honeywell Safety Products Uk Ltd

Edison Rd Basingstoke RG21 6QD United Kingdom Phone: +44 (0) 1256 693 200 Fax: +44 (0) 1256 693 300 Email: info-uk.hsp@honeywell.com

INTERNATIONAL

Honeywell Safety Products Europe SAS

Immeuble Edison Paris Nord 2 33, rue des Vanesses – CS 55288 Villepinte 95958 Roissy CDG Cedex – France Phone: +33 (0)1 49 90 79 79 Fax: +33 (0)1 49 90 71 04 Email: info-export.hsp@honeywell.com

www.honeywellsafety.com

FOR TECHNICAL QUESTIONS INDUSTRIAL SAFETY PPE TECHNICAL SUPPORT

Free Phone: 00 800 3344 2803 (free calls in Europe) Phone: +44 (0) 1698 647 087 (paid calls) Email: IS.PPE.TECHSUPPORT.EUROPE@honeywell.com

07-18-560 GB - 10/2018 ©2018 Honeywell International Inc.

